

INK TANK SYSTEM PRINTER ECOTANK L5190





Print, scan, copy, fax and connect with ease. The economical, multi-function EcoTank L5190 sports a variety of features that makes it the ideal printer for business. Save on printing with Epson's affordable ink bottles, designed for spill- and error-free refilling via designated nozzles on the L5190's integrated ink tanks. Enjoy a full suite of connectivity features such as Wi-Fi, Wi-Fi Direct and Ethernet. Choose the complete printing solution for business now.

















Each printer comes bundled with a starter kit of 4 bottles of Epson genuine inks.

IT'S IN THE DETAILS.





Low Cost, High Yield

Save as you print with affordable ink bottles and an ultra-high page yield of 7,500 pages for colour prints and 4,500 pages for black-and-white prints.

Wireless Connectivity

Print wirelessly over networks or connect to other smart devices with the integrated Wi-Fi and Wi-Fi Direct functions.

Borderless Printing

Print high quality borderless photos up to 4R size.



SPECIFICATIONS

ECOTANK L5190



MODEL NUMBER	
Printer Type	Print, Scan, Copy, Fax with ADF
Printing	On the world in high (Change Lastria)
Printing Technology Nozzle Configuration	On-demand inkjet (Piezoelectric) 180 nozzles Black, 59 nozzles per colour (Cyan, Magenta, Yellow)
Print Direction	Bi-directional printing
Maximum Resolution	5760 x 1440 dpi (with Variable-Sized Droplet Technology)
Minimum Ink Droplet Volume	3 pl
Print Speed ¹	
Draft Text - Memo, A4 (Black#1 / Colour#2)	Up to 33 ppm / 15 ppm
ISO 24734, A4 (Black / Colour) First Page Out Time (Black / Colour)	Up to 10 ipm / 5.0 ipm
Photo Default – 10 x 15 cm / 4 x 6" *2 #3	Approx. 10 sec / 16 sec Approx. 69 sec per photo (Border) / 90 sec per photo (Borderless)
Printer Language	ESC / P-R
Automatic 2-sided printing	No
Copying	
Copy Speed	
ISO 29183, A4, Simplex (Black / Colour)	Up to 7.7 ipm / 3.8 ipm
Copy Quality	Draft / Standard / Best Quality
Maximum Copies from Standalone	99 copies
Reduction/Enlargement	25 – 400 %, Auto Fit Function
Maximum Copy Resolution	600 x 600 dpi
Maximum Copy Size	Legal
Scanning	
Scanner Type	Flatbed colour image scanner CIS
Sensor Type Optical Resolution	CIS 1200 x 2400 dpi
Maximum Scan Area	216 x 297 mm (8.5 x 11.7")
Scanner Bit Depth	
Colour	48-bit input, 24-bit output
Grayscale	16-bit input, 8-bit output
Black & White Scan Speed (Flatbed / ADF (Simplex))	16-bit input, 1-bit output
Monochrome 200 dpi	12 sec / 4.5 ipm
Colour 200 dpi	29 sec / 4.5 ipm
Fax Function	
Type of FAX Receive Memory / Page Memory	Walk-up black-and-white and colour fax capability 1.1 MB, Page memory up to 100 pages
Error Correction Mode	ITU-T T.30
FAX speed (data transfer rate)	Up to 33.6 kbps, Approx. 3 sec/page
FAX Resolution	Up to 200 x 200 dpi
Transmission Paper Size	<u> </u>
Flatbed	Letter, A4
ADF	A4, Letter, Legal, Oficio 9, Mexico-Oficio, Indian-Legal, 8.5 x 13"
Receiving Paper Size Speed Dial / Group Dial	A4, Letter, Legal Up to 100 numbers, 99 groups
Fax Features	PC Fax (Transmission / Receive), Automatic Redial, Address book, Broadcast Fax (Mono Only), Transmit Reservation, Polling Reception
ADF Function	TOTAX (Italianiacon) Trocoroj, raconado racida, racidado boors, bracadast ax (Italia o Tily), incidinistrocorrados, rolling racopadir
Support Paper Thickness	64 – 95 g/m ²
Paper Capacity	30 pages (A4), 10 pages (Legal)
Paper Handling	
Paper Feed Method	Friction feed
Number of Paper Trays Paper Hold Capacity	1
Input Capacity	Up to 100 sheets-A4 / Letter Plain paper (80 g/m²), Up to 20 sheets-Premium Glossy Photo Paper, 10 sheets-Envelope, 30 sheets-Postcard
Output Capacity	30 sheets A4 Plain Paper, 20 sheets Premium Glossy Photo Paper
Paper Size	Legal, Indian-Legal (215 x 345 mm), 8.5 x 13", Letter, A4, 16K (195 x 270 mm), B5, A5, B6, A6, Hagaki (100 x 148 mm), 5 x 7",
	4 x 6", Envelopes: #10, DL, C6
Maximum Paper Size	4 x 6", Envelopes: #10, DL, C6 215.9 x 1200 mm (8.5 x 47.24")
Print Margin	
Print Margin Interface	215.9 x 1200 mm (8.5 x 47.24*) 0 mm top, left, right, bottom via custom settings in printer driver *3
Print Margin Interface USB	215.9 x 1200 mm (8.5 x 47.24*) 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0
Print Margin Interface USB Network	215.9 x 1200 mm (8.5 x 47.24*) 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct
Print Margin Interface USB Network Network Protocol	215.9 x 1200 mm (8.5 x 47.24*) 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6
Print Margin Interface USB Network Network Protocol Network Management Protocols	215.9 x 1200 mm (8.5 x 47.24*) 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct
Print Margin Interface USB Network Network Protocol	215.9 x 1200 mm (8.5 x 47.24*) 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6
Print Margin Interface USB Network Network Protocol Network Management Protocols Mobile and Cloud Printing	215.9 x 1200 mm (8.5 x 47.24*) 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD
Print Margin Interface USB Network Network Protocol Network Management Protocols Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel	215.9 x 1200 mm (8.5 x 47.24*) 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, Mopria Print Service
Print Margin Interface USB Network Network Protocol Network Management Protocols Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen	215.9 x 1200 mm (8.5 x 47.24*) 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD Epson iPrint, Epson Email Print, Remote Print Driver
Print Margin Interface USB Network Network Protocol Network Management Protocols Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software	215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, Mopria Print Service 1.44" Colour LCD
Print Margin Interface USB Network Network Protocol Network Management Protocols Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen	215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, Mopria Print Service 1.44" Colour LCD Windows XP / Vista / 7 / 8 / 8.1 / 10
Print Margin Interface USB Network Network Protocol Network Management Protocols Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software	215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, Mopria Print Service 1.44" Colour LCD
Print Margin Interface USB Network Network Protocol Network Management Protocols Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software	215.9 x 1200 mm (8.5 x 47.24*) 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, Mopria Print Service 1.44* Colour LCD Windows XP / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016
Print Margin Interface USB Network Network Protocol Network Management Protocols Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility Electrical Specifications	215.9 x 1200 mm (8.5 x 47.24*) 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD Epson IPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, Mopria Print Service 1.44* Colour LCD Windows XP / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are supported for Windows Server OS Mac OS X 10.6.8 or later
Print Margin Interface USB Network Network Protocol Network Management Protocols Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility Electrical Specifications Rated Voltage	215.9 x 1200 mm (8.5 x 47.24*) 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, Mopria Print Service 1.44* Colour LCD Windows XP / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are supported for Windows Server OS Mac OS X 10.6.8 or later AC 220 – 240 V
Print Margin Interface USB Network Network Protocol Network Management Protocols Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility Electrical Specifications Rated Voltage Rated Frequency	215.9 x 1200 mm (8.5 x 47.24*) 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD Epson IPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, Mopria Print Service 1.44* Colour LCD Windows XP / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are supported for Windows Server OS Mac OS X 10.6.8 or later
Print Margin Interface USB Network Network Protocol Network Protocols Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility Electrical Specifications Rated Voltage Rated Frequency Power Consumption	215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, Mopria Print Service 1.44" Colour LCD Windows XP / Vista / 7 / 8 / 8.1 / 10 Windows SYP / Vista / 7 / 8 / 8.1 / 10 Windows Standard and scanning functions are supported for Windows Server OS Mac OS X 10.6.8 or later AC 220 – 240 V 50 – 60 Hz
Print Margin Interface USB Network Network Protocol Network Management Protocols Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating	215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD Epson IPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, Mopria Print Service 1.44" Colour LCD Windows XP / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are supported for Windows Server OS Mac OS X 10.6.8 or later AC 220 – 240 V 50 – 60 Hz
Print Margin Interface USB Network Network Protocol Network Management Protocols Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby	215.9 x 1200 mm (8.5 x 47.24*) 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, Mopria Print Service 1.44* Colour LCD Windows XP / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are supported for Windows Server OS Mac OS X 10.6.8 or later AC 220 – 240 V 50 – 60 Hz 12 W 4.3 W
Print Margin Interface USB Network Network Protocol Network Management Protocols Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep	215.9 x 1200 mm (8.5 x 47.24*) 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, Mopria Print Service 1.44* Colour LCD Windows XP / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are supported for Windows Server OS Mac OS X 10.6.8 or later AC 220 – 240 V 50 – 60 Hz 12 W 4.3 W 0.7 W
Print Margin Interface USB Network Network Protocol Network Management Protocols Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep Power off	215.9 x 1200 mm (8.5 x 47.24*) 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, Mopria Print Service 1.44* Colour LCD Windows XP / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are supported for Windows Server OS Mac OS X 10.6.8 or later AC 220 – 240 V 50 – 60 Hz 12 W 4.3 W
Print Margin Interface USB Network Network Protocol Network Protocols Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep Power off Noise Level	215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, Mopria Print Service 1.44" Colour LCD Windows XP / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are supported for Windows Server OS Mac OS X 10.6.8 or later AC 220 – 240 V 50 – 60 Hz 12 W 4.3 W 0.7 W 0.3 W
Print Margin Interface USB Network Network Protocol Network Management Protocols Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep Power off Noise Level Premium Glossy Photo / Paper Best Photo	215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD Epson IPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, Mopria Print Service 1.44" Colour LCD Windows XP / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are supported for Windows Server OS Mac OS X 10.6.8 or later AC 220 – 240 V 50 – 60 Hz 12 W 4.3 W 0.7 W 0.3 W Sound Power (Black / Colour) 5.2 B(A), Sound Pressure (Black / Colour) 38 dB(A) / 39 dB(A)
Print Margin Interface USB Network Network Protocol Network Protocols Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep Power off Noise Level	215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, Mopria Print Service 1.44" Colour LCD Windows XP / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are supported for Windows Server OS Mac OS X 10.6.8 or later AC 220 – 240 V 50 – 60 Hz 12 W 4.3 W 0.7 W 0.3 W Sound Power (Black / Colour) 5.2 B(A), Sound Pressure (Black / Colour) 38 dB(A) / 39 dB(A) Sound Power (Black / Colour) 6.5 B(A) / 6.3 B(A), Sound Pressure (Black / Colour) 52 dB(A) / 50 dB(A)
Print Margin Interface USB Network Network Protocol Network Management Protocols Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep Power off Noise Level Premium Glossy Photo / Paper Best Photo Plain Paper Default*4	215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, Mopria Print Service 1.44" Colour LCD Windows XP / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are supported for Windows Server OS Mac OS X 10.6.8 or later AC 220 – 240 V 50 – 60 Hz 12 W 4.3 W 0.7 W 0.3 W Sound Power (Black / Colour) 5.2 B(A), Sound Pressure (Black / Colour) 38 dB(A) / 39 dB(A) Sound Power (Black / Colour) 6.5 B(A) / 6.3 B(A), Sound Pressure (Black / Colour) 52 dB(A) / 50 dB(A) Page Yield*s Order Code
Print Margin Interface USB Network Network Protocol Network Protocols Mobile and Cloud Printing Eson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep Power off Noise Level Premium Glossy Photo / Paper Best Photo Plain Paper Default'4 Consumables	215.9 x 1200 mm (8.5 x 47.24") 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, Mopria Print Service 1.44" Colour LCD Windows XP / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are supported for Windows Server OS Mac OS X 10.6.8 or later AC 220 – 240 V 50 – 60 Hz 12 W 4.3 W 0.7 W 0.3 W Sound Power (Black / Colour) 5.2 B(A), Sound Pressure (Black / Colour) 38 dB(A) / 39 dB(A) Sound Power (Black / Colour) 6.5 B(A) / 6.3 B(A), Sound Pressure (Black / Colour) 52 dB(A) / 50 dB(A) Page Yield*s Order Code
Print Margin Interface USB Network Network Protocol Network Protocols Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sieep Power off Noise Level Premium Glossy Photo / Paper Best Photo Plain Paper Default*4 Consumables Black Ink Bottle	215.9 x 1200 mm (8.5 x 47.24*) 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, Mopria Print Service 1.44* Colour LCD Windows XP / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are supported for Windows Server OS Mac OS X 10.6.8 or later AC 220 – 240 V 50 – 60 Hz 12 W 4.3 W 0.7 W 0.3 W Sound Power (Black / Colour) 5.2 B(A), Sound Pressure (Black / Colour) 38 dB(A) / 39 dB(A) Sound Power (Black / Colour) 6.5 B(A) / 6.3 B(A), Sound Pressure (Black / Colour) 52 dB(A) / 50 dB(A) Page Yield*s Order Code 4,500 003
Print Margin Interface USB Network Network Protocol Network Protocols Mobile and Cloud Printing Epson Connect Other Mobile Solutions Control Panel LCD Screen Printer Software Operating System Compatibility Electrical Specifications Rated Voltage Rated Frequency Power Consumption Operating Standby Sleep Power off Noise Level Premium Glossy Photo / Paper Best Photo Plain Paper Default ⁴ Consumables Black Ink Bottle Cyan Ink Bottle	215.9 x 1200 mm (8.5 x 47.24*) 0 mm top, left, right, bottom via custom settings in printer driver *3 USB 2.0 Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct TCP/IPv4, TCP/IPv6 SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD Epson iPrint, Epson Email Print, Remote Print Driver Apple AirPrint, Google Cloud Print, Mopria Print Service 1.44* Colour LCD Windows XP / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016 Only printing and scanning functions are supported for Windows Server OS Mac OS X 10.6.8 or later AC 220 – 240 V 50 – 60 Hz 12 W 4.3 W 0.7 W 0.3 W Sound Power (Black / Colour) 5.2 B(A), Sound Pressure (Black / Colour) 38 dB(A) / 39 dB(A) Sound Power (Black / Colour) 6.5 B(A) / 6.3 B(A), Sound Pressure (Black / Colour) 52 dB(A) / 50 dB(A) Page Yield*s Order Code 4,500 003 003

Dimensions & Weight 15190 Weight: 5.0 kg / 11.0 lbs



*1 Print speed (Pages Per Minute) is calculated when printed on A4 plain paper in the fastest mode, 10 x 15 cm photo print speed when printed on Epson Premium Glossy Photo Paper. Print speed may vary depending on system configuration, print mode, document complexity, software, type of paper used and connectifyl. Print speed does not include processing time on host computer.







#1 Black Text

#2 Black Text and graphics

(

- *2 When printed on Epson Premium Glossy Photo Paper
- $^{*}3$ Borderless printing is supported up to 4R (4 x 6"), otherwise 3 mm top, left, right, bottom.
- *4 Default mode in accordance with ISO7779.
- 4 Default mode in accordance with ISO7779.
 5 Quoted yields are based on the ISO 24711/24712 patterns of mixed text and colour graphics with Epson methodology. Quoted yields are based on the replacement ink bottles purchased. For print quality, part of the ink from the included bottles is used for printer startup so yields could be lower than those of replacement link bottles. Actual yields will vary due to reasons including images printed, print settings, temperature and humidity. Yields may be lower when printing infrequently or predominantly with one ink colour. Ink is used for both printing and printhead maintenance. All inks are used for both black and colour printing.

© 2019 Epson Singapore Pte Ltd. All Rights Reserved. © 2019 Epson Singapore Pte Ltd. All Rights Reserved.
Reproduction in part or in whole, without the written
permission from Epson, is strictly prohibited. EPSON and
EXCEED YOUR VISION are registered trademarks of Seiko
Epson Corporation. All other products names and other
company names used herein are for identification purposes
only and are the trademarks or registered trademarks of
their respective owners. Epson disclaims any and all rights
in those marks. Print samples shown are simulations only.
Specifications and product availability are subject to change
without notice and may vary between countries. Please
check with local Epson offices for more information.
Applie 18-94 and 18-pose are trademarks of Apple Inc.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Dealer's Stamp

Information correct at time of printing Printed June 2019

Sales Enquiries 800 120 5564 FEDSONSEA O EDSONSEA FEDSONSEA YOUTUBE EDSONSOUTHEASTASIA IN EDSON SOUTHEAST ASIA









For latest specifications, visit www.epson.com.sg/ecotank or call 800 120 5564.

Epson Singapore Pte Ltd 1 Harbourfront Place, #03-02 HarbourFront Tower One, Singapore 098633. Tel: (65) 6586-5500 Fax: (65) 6271-9755

Epson Customer Care Centre 108, Pasir Panjang Road, #04-08 Golden Agri Plaza, Singapore 118535. Epson Helpdesk: 800 120 5564. Operating hours: Monday – Friday, 9am – 6pm, Saturday, 9am – 1pm. Closed on Sunday and Public Holiday.